

Product Information

Mod.R&S 06 | Rev.4 | Update 08/2019 | Page 1




SPARKLE

Description PU plotter cut heat seal material with high thickness glitters and adhesive polyester backing. Specifically conceived for fashionwear.

> Suitable for cotton, polyester, poly/cotton blends, elastic fabrics and spandex (not suited for treated and sublimated textiles).

- **Usage** Mirror cut the material
 - Weed the exceeding material
 - Place the material on the garment with its polyester backing
 - Heat apply at the conditions shown on the right
 - Remove the carrier warm





Suggested cutting settings

Blade: 45° Pressure: 80 gf Speed: 25 cm/sec



Transfer settings

15 seconds at 155°C (311°F) medium pressure (3-4 bar)

Washing Wait at least 24 hours from application before washing. Washing resistance up to 60°C, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Suitable for tumble dryer, cotton cycle.

The product is REACH compliant

Washing temperature



Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience. We always recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight at temperatures between 65°F and 80°F



Management System ISO 9001:2015 ISO 14001:2015



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations. Updated versions are available on our website www.siser.com

For further information, please contact our Sales Office.

