

***COLORPRINT***  
***Digital printing material***

<p><b>Description</b></p>	<p>Material specifically formulated for thermoresin, ink jet solvent and eco solvent based inks – printing and cutting systems. Polyester backing.</p>
<p><b>Tips</b></p>	<p>Certified by Roland® for VersaCamm SP-300 and Ink Jet printers using eco solvent based inks</p> <p>We suggest to let the print drying (at least 12 hours) before rolling, overlaying or heat transferring the material. We highly recommend application and washing test.</p>
<p><b>Application instructions</b></p>	<ol style="list-style-type: none"> <li>1) Print and cut the material</li> <li>2) Let the print dry at least 12 hours.</li> <li>3) Weed and remove image from backing with an hot resistant application tape. <b>We recommend to use the Siser transparent polyester TTD</b></li> <li>4) Heat apply following the below indicated conditions</li> <li>5) Remove application tape once <b>cold</b></li> </ol> <p>Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:</p>
<p><b>Temperature:</b> <b>Time:</b> <b>Pressure:</b> <b>Washable to:</b></p>	<p>150°C 10 – 15 sec. medium 50°C</p>

**SIZES AND COLOURS**

<b>ROLLS</b>	width 1,50 m.	length 25 m.
	width 0,50 m.	length 25 m.
<b>COLOURS</b>	white	