

SUBLITHIN MATT™

Description

Digital printing material for ink jet solvent and eco solvent based inks – printing and cutting systems for application onto dyed garments (sublimation inks). The special formulation and processing of the material create a barrier to the dyes of the textile avoiding the sublimation bleed: decoration colour won't change along time.

Polyester backing.

Basic Information

Due to the many different plotter machines and base materials available on the market, the following heat transfer instructions are given as guideline only:

Cutting (ex. Roland plotter VP300) **Blade:** new at 45° **Minimum required cutting pressure:** 80gf

Application **Temperature:** 155°C **Time:** 15" **Pressure:** medium (3±4 bar)

Application Instructions

- 1) Print and cut the material
- 2) Weed the exceeding material
- 3) Remove the image from the backing using the **Siser transparent polyester T.T.D. Advanced** (adhesive, transparent polyester, resistant to high temperatures) or other application tapes
- 4) Heat apply
- 5) Remove application tape **hot**. Should you use other application tapes, follow the manufacturer's instructions

Suitable for

Polyester fabrics dyed with sublimation inks

Washing: (wait 24h after the heat transfer)

30°C Max. – wash inside out - do not use bleach or other aggressive chemical agents

Dry-cleaning : no

Tumble drier : not advisable

N.B. : all information given in this sheet are based on our experience

We recommend to always perform a test before starting standard production

The product meets the Italian and Ue regulations relating to its proper use.

This document can be subject to variations. Updated versions are available on our website www.siser.it.

For further information, please contact our Sales Office. Thank you.

SISER s.r.l.

V.LE DELLA TECNICA n. 18 – 36100 VICENZA ITALY

TEL. +39 0444 287960 - FAX +39 0444 287959 - E-mail: info@siser.it - www.siser.it

R.E.A. VI 171856 VI – Reg. Imp. VI n. 14971 - Cap. Soc. € 103.300 i.v. – Partita IVA 01591490246



Organizzazione con sistema di gestione certificato
ISO 9001:2008