

# Utopia SV25

## Sand Textured Overlamine



### Product Information

<b>Adhesive:</b>	Permanent Acrylic Based
<b>Film:</b>	Matt textured, 0.15 ± 0.010mm
<b>Liner:</b>	Kraft Paper, 80gsm, 0.120 ± 0.010mm
<b>Durability:</b>	Vertical Exposure Up To 3 Years

### Description

Utopia SV25 Sand Textured style Overlamine (also known as Sandtex) is versatile enough for a broad variety of signage and display applications. As well as being used as the most traditional form of protection for pull-up and pop-up display stands. Utopia SV25 sand textured overlamine also benefits from being certified by Australian and New Zealand Standards (AS/NZS 4586:2004) for wet and dry slip resistance.

### Applications

Floor graphics, pull-up displays, point of sale, display graphics (indoor and outdoor), wall laminates and posters.

Product Features	SV25	Test Method
Length	Standard Length 50m/roll	
Width	Standard Width 1295mm	
Facefilm	Matt textured, 0.15 ± 0.010mm	
Liner	White, Kraft Paper, 0.120 ± 0.010mm	
Liner Weight	80gsm single sided PE	
Adhesive	Pressure Sensitive Solvent Based Acrylic	
Initial Adhesion	No. 10-20	J.Dow method
Cohesion Holding Power	24Hr	2cm x 2cm x 1kg, at 25°C
Ultimate Adhesion	Stainless Steel 1.0kg/inch	180° Peel Adhesion
Slip Resisitance	Wet & Dry	AS/NZS 4586:2004
Shelf Life	1 Year	Stored at 5°C-40°C/35-75% RH

**PLEASE NOTE** – All information, recommendations and suggestions contained herein, without limitation, stated values (collectively the “information”) shall be used only as a guide by Purchaser and not for specification or any other purpose. The information does not constitute a warranty or guaranty of any type whatsoever. Purchase should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own tests. No liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser’s reliance on the information.