



The applications are endless...

DPF 4500G Vinyl Film

Intermediate Calendered Digital Print Pressure Sensitive Film

DPF 4500G is a 3-mil clear calendered film with permanent pressure-sensitive adhesive. Designed for indoor and outdoor promotional graphics, DPF 4500G is made of 100% polymeric face stock with a clay-coated kraft liner. The special glossy face stock is designed for applications requiring High Gloss or more image “pop”. DPF 4500G is rated for outdoor durability up to 5 years (unprinted). Printed durability is dependent on the ink system used.

AREAS OF USE

- Digital printing with a wide variety of direct print systems, including Encad® VinylJet™
- Promotional and merchandising graphics
- Shorter-term signage, kiosks, POP displays, real estate signage, transit graphics, vehicle markings and decals

PERFORMANCE AND PHYSICAL DATA

PROPERTY	TEST METHODS	TYPICAL VALUE	
SURFACE FINISH	Gloss Meter 60° Reflection	80-90%	
THICKNESS (including adhesive)	Micrometer, Federal Bench Type	0.0043 in	0.11 mm
TENSILE STRENGTH	Tensile Tester with 2-in (51 mm) jaw separation; crosshead speed of 12 in/min. (5.1 mm/s), web direction	13.0 lb/in width	2.3 kg/cm width
ELONGATION	Instron Tensile Tester as above	≥ 150%	
SHELF LIFE	Free from excessive moisture, temperature, direct sunlight	1 year from factory shipment	
APPLICATION TEMPERATURE RANGE	On clean, dry substrate	60°F to 90°F optimum	16°C to 32°C optimum
SERVICE TEMPERATURE RANGE	On clean, dry substrate	-20°F to 150°F	-29°C to 65°C
DIMENSIONAL STABILITY	158°F (70°C), 48 hours	25 mils	0.64 mm
PEEL ADHESION	PSTC-1, 15 min, RT 70°F (21°C)	2.5 lbs/in	0.45 kg/cm
LINER RELEASE	TLMI Release at 90°, 300 in/min (760 cm/min)	100 g/2 in width	39 g/cm

*Standard Terms and Conditions Apply

Effective 06.09

TERMS AND
CONDITIONS

The following is made in lieu of all warranties expressed or implied:

All statements, technical information and recommendations published by Arlon, Inc. relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon, Inc. makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon, Inc. shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.