



High Performance Grade Vinyl for Solvent Inkjet Printing

Product Description

Metamark MD5 is a high performance grade polymeric calendered self-adhesive vinyl for printers using solvent inks. The high quality film, release paper and adhesive, combined with Metamark's distinctive coating technology provides outstanding print performance. MD5 is supplied with a solvent-based adhesive.

Typical Applications

MD5 can be used for interior and exterior application onto flat or slightly curved surfaces, such as vehicle graphics, retail signage and window graphics. The solvent-based adhesive eliminates problems of milky residue during wet application.

Material Processing and Handling

To achieve the highest possible print quality please ensure that the correct profile is used. Most profiles are available and can be downloaded from www.metamark.co.uk. To avoid potential printing problems, always ensure that the material has reached room temperature and a relative humidity of 50% before printing. It is imperative that the printer is set up correctly and that the correct profile and heater settings are used. Do not handle the face film directly and ensure it is free from dust and static. For a comprehensive list of printers compatible with MD5 Digital Vinyl refer to the website. Solvents from the printing process may initially cause the vinyl to soften and may initially reduce the strength of the adhesive, so after printing, leave 24 hours before applying the material and for the adhesive to regain full strength.

Face Film		Finishes			
Face Film Gauge Tensile Strength	Polymeric calendered PVC 70 micron nominal 47N/25mm MD / 43N/25mm TD nominal	Finishes Available	MD5-100 MD5-101 MD5-105	White Gloss White Matt Clear Gloss	
Elongation at break	180% MD nominal	Roll Presentation			
Adhesive	Dermanant clear pressure consitius	Roll sizes and net weights	760mm x 50m 1370mm x 50m 1520mm x 50m	11kg 20kg	
Туре	Permanent clear pressure sensitive solvent-based acrylic		1600mm x 50m	22kg 23kg	
Weight Adhesion to glass 20 mins Adhesion to glass 24 hour	22gsm nominal 15N/25mm nominal 20N/25mm nominal	Presentation	Face film outwards, on a 76mm core.		
Perceived tack	Medium	Durability			
Shear strength Application temperature Service temperature	Medium to high +5°C to +60°C -30°C to +110°C	Shelf Life External weathering	2 years 7 years. *This refers to the unprinted vinyl when installed. Refer to ink		
Release Liner			manufacturer for di		
Print Weight Type	'Metamark Digital Vinyl' grey print 140 gsm nominal Advanced specially treated layflat kraft paper with high internal strength and PE coating MD: Machine direction, TD: Transverse direction	Fire Rating	finished product. Class B. Classification compliant with BS EN 13501-1:2007 European standard. The full classification is 'B / s2 / d0'. Only applies when applied to substrates of a density greater than or the same as plasterboard, 800kg/m³. See web site for further information		

Warranty: Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Digital Vinyl will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark Digital Vinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair.

Please Note: The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.